



INNOVATING **NUCLEAR** TECHNOLOGY
ANALYSIS AND MEASUREMENT SERVICES CORPORATION

Advanced Process Instrumentation System for Next-Generation Nuclear Reactors



Presented by:
Ryan O'Hagan
Sr. Engineer and Marketing Manager

Presented to:
DOE-NE FY23 ASI Program Annual Review Webinar

November 1st, 2023






We Test the I&C Systems of Nuclear Power Plants



- All U.S. nuclear power plants
- Nuclear plants in Europe, Asia, Africa, Middle East, and South America
- Government Facilities including Y-12, Sandia, Savannah River, HFIR/ORNL, and ATR/INL



I&C MAINTENANCE




ROD CONTROL



CABLE TESTING



SOFTWARE RELIABILITY



EMC/WIRELESS



REACTOR DIAGNOSTICS



MATERIALS TESTING



ONLINE MONITORING

- **Harsh process conditions**

- Elevated temperatures
- High radiation
- Corrosive coolants



- **Limited hands-on maintenance**

- Extended refueling cycles
- Online refueling
- Remote installation (limited on-site staff)

- **Physical design constraints**

- Compact containment vessel
- Integral reactor (no loops / piping)

Reactor	Type	Coolant	Output	Temperature	Refueling/Cycle
NuScale VOYGR	iPWR SMR	Water	77 MWe	300°C	24 Months
Holtec SMR-160	PWR SMR	Water	160 MWe	316°C	42 Months
GE Hitachi BWRX-300	BWR SMR	Water	300 MWe	287°C	12-24 Months
TerraPower MCFR	MSR	Molten Salt	780 MWe	755°C	Online
TerraPower Natrium	SFR	Sodium	≥ 345 MWe	540°C	24 Months
X-Energy Xe-100	PB HTGR	Helium	80 MWe	565°C	Online
Kairos Power FHR	PB MSR	Molten Salt	140 MWe	650°C	Online
Ultra Safe Nuclear MMR	Micro-HTGR	Helium	5 MWe	630°C	20 Years
Westinghouse eVinci	Heat-Pipe MR	N/A	1-5 MWe	> 750°C	48-60 Months
Oklo Aurora	Heat-Pipe MR	N/A	1.5 MWe	> 500°C	20 Years
BWXT BANR	Micro-HTGR	Gas	17 MWe	> 750°C	5 Years
General Atomics	HTGR	Helium	50 MWe	800°C	104 Months
ARC-100	SFR SMR	Sodium	100 MWe	510°C	20 Years

PWR – pressurized water reactor, iPWR – integral PWR, BWR – boiling water reactor, MSR – molten salt reactor, SFR – sodium-cooled fast reactor, HTGR – high-temperature gas-cooled reactor, PB – pebble bed



STTR R&D Objective & Project Team

Objective: Develop a sensor incorporating the HTIR-TC developed at INL that can measure temperature, flow, and level simultaneously in harsh next-generation reactor environments

AMS Executive Research Advisory Team



H.M.
Hashemian



Greg
Morton



Brent
Shumaker



Casey
Sexton



Chad
Kiger

AMS STTR R&D Team



Alexander
Hashemian (PI)



Jacob
Houser



Shawn
Tyler



Edwin
Riggsbee



Dan
McCarter



Keith
Ryan


INL R&D Scientist




Dr. Richard
Skifton

Background of the INL HTIR-TC

- Developed for use in materials testing reactors
- Demonstrated in INL Advanced Test Reactor (AGR-5/6/7)
- Winner of 2019 R&D100 Award
- Qualified through DOE-NE ASI Program
- Licensed to Idaho Laboratories Corp. in 2020 through SBIR award





*Patent Pending (Skifton, Daw – USPTO Application US16/690,630)





Prototype Sensor Design

- 0.25-inch diameter, 4-ft length
- 8x Thermocouples
 - 4x grounded-junction HTIRs
 - 4x ungrounded-junction Type-K TCs
- 1x 4-Wire Self-Heated RTD



Natural fluctuations (noise) in sensor output can be analyzed to:

- Determine sensor response time
- Identify blockages in sensing lines (using pressure transmitter data)
- Quantify core barrel vibration (ex-core neutron detectors)
- **Measure RCS flow via transit time flow measurement (TTFM)**



Transit Time Flow Measurement:

- Requires at least one up/down-stream sensor (can be “unlike” sensors)
- Demonstrated by AMS using RTDs, TCs, neutron detectors
- Accuracy dependent on plant process conditions and sensor characteristics




INL and AMS Sensor Test Facilities

- **INL Flowing Autoclave System (FAS)**



- Water-filled test loop
- Up to 608°F and 2500 PSI

- **AMS Thermal-Hydraulic Test Loop**

- Water-filled test loop
- Up to 200°F and 200 PSI



Custom Built Testbed for Prototype Sensor






Actual Flow	Average Calculated Flow	Percent Error
0.100 ft/s	0.108 ft/s	7.8 %
0.200 ft/s	0.193 ft/s	-3.5 %



Key Accomplishments of the STTR Project

- Demonstrated TTFM using HTIR-TCs for flowing water and air processes
- Designed and built a new custom testbed for prototype sensor testing at AMS
- Designed a prototype multi-element sensor probe (fabricated by Idaho Laboratories Corp) and determined baseline sensor performance through laboratory testing – patent pending
- Established software and sensor data acquisition system hardware requirements



➤ **DOE Phase 2 SBIR: Online Monitoring (OLM) for Autonomous Microreactors**


Objective: Develop OLM for microreactor sensors, equipment, processes, and SSCs

- Evaluate AI/ML techniques for fault detection, diagnostics, prognostics
- Produce and demonstrate prototype OLM system for microreactors

➤ **DOE Phase 2 SBIR: Development of Cable Insulation Materials for Advanced Reactors**

GOAL: Identify suitable cable insulation materials for Advanced Reactors

- Subject potential insulation materials to SMR/Adv Rx conditions
- Measure material properties to determine suitability for use



Recently Concluded Projects

Program	Project Title
SBIR	I&C System Design for SMRs
	Methods for Verifying Embedded Sensor Performance in AM Components
GAIN	Cable Derating and Survivability, Sensor Performance Characterization at SMR Conditions
	Radiation Aging of Nuclear Power Plant Components



AMS Materials Test Laboratory



INNOVATING *NUCLEAR* TECHNOLOGY

ANALYSIS AND MEASUREMENT SERVICES CORPORATION

Thank You

Questions?

